




Silver

### SILVER



6"x36"



3"x18" Bullnose

### BRONZE



6"x36"



3"x18" Bullnose




Magma

### TILDEN GRAY



6"x36"



3"x18" Bullnose

### MAGMA



6"x36"



3"x18" Bullnose



BARNWOOD		
Technical Specifications Reference Standard	Standard Requirements	Test Results
Water Absorption UNI EN ISO 10545-06	< 0.5 %	0.55 %
Breaking Strength UNI EN ISO 10545-04	Minimum : 3300 N	3332 N
Modulus of Rupture UNI EN ISO 10545-04	Minimum : 35 N/mm <sup>2</sup>	Complies
Shock Resistance UNI EN ISO 10545-06	Suggested Minimum : >= 40.55	Complies
Resistance to Deep Abrasion UNI EN ISO 10545-06	Minimum : 375 mm <sup>3</sup>	Complies
Thermal Linear Expansion UNI EN ISO 10545-05	Minimum for Floor Applications: Class 1	Complies
Thermal Shock Resistance UNI EN ISO 10545-09	Resistant	Complies
Moisture Expansion UNI EN ISO 10545-10	As Reported	0.1 mm/m
Frost Resistance UNI EN ISO 10545-10	As Reported	Complies
Chemical Resistance UNI EN ISO 10545-13	Detergent, Chemical Products & FOGS, Acids and Alkalis As Reported	GA CLA
Stain Resistance UNI EN ISO 10545-14	Minimum : Class 3	5
PEI Rating (scratch Resistance) AS/NZS 4107	As Reported	PEI IV
Static Coefficient of Friction (COF) AS/NZS 4107	Per Level Institute Standard Expected to be Met/Not Met Upon Water Wet: > 0.60	DRY: > 0.65 WET: > 0.60
Dynamic Coefficient of Friction (DCOF) ANSI A137.1	Per Level Institute Standard Expected to be Met/Not Met Upon Water Wet: > 0.42	0.60
Shade Variation Not Available	As Reported	1%2
Thickness Not Available	As Reported	9.7 mm
Number of Screens Not Available	As Reported	3 + mix

Following EN 14411 (ex iso 13006) norms and test cases UNI ISO 10545 appendix G for ceramic tiles dry pressed with low water absorption E < 0.5 % group B1a

**INSTALLATION TIPS**

**1/2 BROKEN JOINT NOT RECOMMENDED. MANUFACTURER RECOMMENDS 1/3 OR LESS STAGGERED SPACING.**

**IMPORTANT**  
Please note that using a 1/2" staggered configuration is not recommended. It is important to follow the configuration in this section carefully.

**NO 30%** **YES 13%**

**DIGITAL INFLUENT TILE**

**HF HAPPY FLOORS**  
www.happy-floors.com

**MADE IN SPAIN**

**CECIB MEMBER**

**I-Design**  
COLLECTION



Tilden Gray