




DOLOMITE				
TECHNICAL CHARACTERISTICS	Reference Standard	Standard Requirements	Test Results	
			NATURAL	POLISHED
Water Absorption	UNI EN ISO 10545-03	<0,5%	E<0,1%	
Breaking strength	UNI EN ISO 10545-04	Minimum: 1300N	>1700	
Modulus of Rupture	UNI EN ISO 10545-4	Minimum: 35N/mm²	>40	
Resistance to abrasion of glazed tiles (PEI)	UNI EN ISO 10545-07	See manufacturer's declaration	CLASSE 4	
Thermal Linear Expansion	UNI EN ISO 10545-08	As Reported	7,5 x10 ⁻⁴ /°C	
Thermal Shock Resistance	UNI EN ISO 10545-09	-	Resistant	
Frost Resistance	UNI EN ISO 10545-12	As Reported	Resistant	
Chemical Resistance	UNI EN ISO 10545-13	Domestic Chemical Products:UB/G8 Acids and Alkalies: As Reported	GA	
			GLA	GLB
Stain Resistance	UNI EN ISO 10545-14	Minimum: Class 3	CLASS 4	
Dynamic Coefficient of Friction (DCOF)	ANSI A137.1	For Level Interior Spaces Expected to be Walked Upon When Wet	WET: >0.42	-
Friction coefficient (slipperiness)	DIN 51130	-	RY	-
	ASTM C1028	-	DRY/WET: >0.6	-
Shade Variation	Not Available	As Reported	V2	
Thickness	UNI EN ISO 10545-02	±5% - ±0,5 mm	±0,5 mm (10mm)	
Number of Screens	Not Available	As Reported	white 24"x48" 10 screens white/beige 14"x32" 12 screens white/beige 12"x24" 16 screens white/beige 24"x24" 8 screens	

≥34%

AMOUNT OF
COLOR
VARIATION
V2
MEDIUM COLOR VARIATION



HAPPY FLOORS



GROUT JOINT REQUIRED FOR RECTIFIED EDGE TILE
1/2" BROKEN JOINT NOT RECOMMENDED



DOLOMITE

Rectified Porcelain



DOLOMITE

Rectified Porcelain



WHITE 24"x48" NATURAL
WHITE 24"x48" POLISHED



WHITE 16"x32" NATURAL
WHITE 16"x32" POLISHED



WHITE 24"x24" NATURAL
WHITE 24"x24" POLISHED



WHITE 12"x24" NATURAL
WHITE 12"x24" POLISHED



WHITE 3"x24" BULLNOSE NATURAL
WHITE 3"x24" BULLNOSE POLISHED



WHITE 2"x2" MOSAIC
12"x12" SHEET NATURAL
WHITE 2"x2" MOSAIC
12"x12" SHEET POLISHED



WHITE PINWHEEL DECO
MOSAIC 12"x12"
SHEET POLISHED



WHITE 3D HEX MOSAIC
7"x12" SHEET POLISHED



WHITE 1"x1" MOSAIC
12"x12" SHEET NATURAL
WHITE 1"x1" MOSAIC
12"x12" SHEET POLISHED



WHITE HEXAGON MOSAIC
12"x14" SHEET NATURAL
WHITE HEXAGON MOSAIC
12"x14" SHEET POLISHED



BEIGE 2"x2" MOSAIC
12"x12" SHEET NATURAL
BEIGE 2"x2" MOSAIC
12"x12" SHEET POLISHED



BEIGE PINWHEEL DECO
MOSAIC 12"x12"
SHEET POLISHED



BEIGE 3D HEX MOSAIC
7"x12" SHEET POLISHED



BEIGE 1"x1" MOSAIC
12"x12" SHEET NATURAL
BEIGE 1"x1" MOSAIC
12"x12" SHEET POLISHED



BEIGE HEXAGON MOSAIC
12"x14" SHEET NATURAL
BEIGE HEXAGON MOSAIC
12"x14" SHEET POLISHED



BEIGE 16"x32" NATURAL
BEIGE 16"x32" POLISHED



BEIGE 24"x24" NATURAL
BEIGE 24"x24" POLISHED



BEIGE 12"x24" NATURAL
BEIGE 12"x24" POLISHED



BEIGE 3"x24" BULLNOSE NATURAL
BEIGE 3"x24" BULLNOSE POLISHED

GROUT JOINT REQUIRED FOR RECTIFIED EDGE TILE
1/2 BROKEN JOINT NOT RECOMMENDED



WHITE



BEIGE



WHITE



BEIGE