



	EXOTIC STONE					
	TECHNICAL CHARACTERISTICS	Reference Standard	Standard Requirements	Test Results		
				NATURAL	POLISHED	
	Water Absorption	UNI EN ISO 10545-03	<0,5%	E<0,1%		
	Breaking strength	UNI EN ISO 10545-04	Minimum: 1300N	>1700		
	Modulus of Rupture	UNI EN ISO 10545-4	Minimum: 35N/mm²	>40		
	Resistance to abrasion of glazed tiles (PEI)	UNI EN ISO 10545-07	See manufacturer's declaration	Lagoon Classe 3 Arctic Classe 4 Fossil Classe 4 Tundra Classe 3		
	Thermal Linear Expansion	UNI EN ISO 10545-08	As Reported	7.5 x10 ⁻⁴ /°C		
	Termal Shocks Resistance	UNI EN ISO 10545-09	-	Resistant		
	Frost Resistance	UNI EN ISO 10545-12	As Reported	Resistant		
	Chemical Resistance	UNI EN ISO 10545-13	Domestic Chemical Products:UB/G8	GA		
			Acids and Alkalis: As Reported	GLA	GLB	
	Stain Resistance	UNI EN ISO 10545-14	Minimum: Class 3	CLASSE 4	CLASSE 3	
DCOF	Dinamic Coefficient of Friction (DCOF)	ANSI A137.1	For Level Interior Spaces Expected to be Walked Upon When Wet	: >0.42	WET: >0.42	-
	Friction coefficient (slipperiness)	DIN 51130	-	R9	-	
	Shade Variation	Not Available	As Reported	V3 - V4		
	Thickness	UNI EN ISO 10545-02	As Reported	±5%		
	Number of Screens	Not Available	As Reported	20x120 (8"x47") 18 screens		
				30x60 (12"x24") 23 screens		



ExoticStone

Porcelain





V3 HIGH
HIGH SHADE VARIATION
WITHIN EACH CARTON.



V4 RANDOM
VERY HIGH SHADE VARIATION
WITHIN EACH CARTON.



HAPPY FLOORS



GROUT JOINT REQUIRED FOR RECTIFIED EDGE TILE
1/2" BROKEN JOINT NOT RECOMMENDED



ExoticStone

TUNDRA



8"x47" Natural RECTIFIED EDGE
8"x47" Polished RECTIFIED EDGE



2,75"x24" Natural Bullnose
2,75"x24" Polished Bullnose

FOSSIL



8"x47" Natural RECTIFIED EDGE
8"x47" Polished RECTIFIED EDGE




2,75"x24" Natural Bullnose
2,75"x24" Polished Bullnose

ARCTIC



8"x47" Natural RECTIFIED EDGE
8"x47" Polished RECTIFIED EDGE




2,75"x24" Natural Bullnose
2,75"x24" Polished Bullnose

LAGOON



8"x47" Natural RECTIFIED EDGE
8"x47" Polished RECTIFIED EDGE



2,75"x24" Natural Bullnose
2,75"x24" Polished Bullnose



12"x24" Natural RECTIFIED EDGE
12"x24" Polished RECTIFIED EDGE



2"x2" Mosaic Natural
(12"x12" Sheet)
2"x2" Mosaic Polished
(12"x12" Sheet)



Hexagon Mosaic Natural
(12"x14" Sheet)
Hexagon Mosaic Polished
(12"x14" Sheet)




Muretto Mosaic Natural
(12"x12" Sheet)
Muretto Mosaic Polished
(12"x12" Sheet)



12"x24" Natural RECTIFIED EDGE
12"x24" Polished RECTIFIED EDGE




2"x2" Mosaic Natural
(12"x12" Sheet)
2"x2" Mosaic Polished
(12"x12" Sheet)



Hexagon Mosaic Natural
(12"x14" Sheet)
Hexagon Mosaic Polished
(12"x14" Sheet)



Muretto Mosaic Natural
(12"x12" Sheet)
Muretto Mosaic Polished
(12"x12" Sheet)



12"x24" Natural RECTIFIED EDGE
12"x24" Polished RECTIFIED EDGE



2"x2" Mosaic Natural
(12"x12" Sheet)
2"x2" Mosaic Polished
(12"x12" Sheet)




Hexagon Mosaic Natural
(12"x14" Sheet)
Hexagon Mosaic Polished
(12"x14" Sheet)



Muretto Mosaic Natural
(12"x12" Sheet)
Muretto Mosaic Polished
(12"x12" Sheet)



12"x24" Natural RECTIFIED EDGE
12"x24" Polished RECTIFIED EDGE



2"x2" Mosaic Natural
(12"x12" Sheet)
2"x2" Mosaic Polished
(12"x12" Sheet)



Hexagon Mosaic Natural
(12"x14" Sheet)
Hexagon Mosaic Polished
(12"x14" Sheet)



Muretto Mosaic Natural
(12"x12" Sheet)
Muretto Mosaic Polished
(12"x12" Sheet)

GROUT JOINT REQUIRED FOR RECTIFIED EDGE TILE
1/2 BROKEN JOINT NOT RECOMMENDED

