



Construction	SPC Rigid Core Loose Lay
Sizes	9" x 60"
Total Thickness	5.2mm SPC 5.0mm LL
Wear Layer	20mil
Protective Coating	UV, Stain, & Scratch
Attached Pad	1mm High Density IXPE Sound Abatement SPC
Edge Profile	Micro Bevel
Installation Method	Rigid Core Floating Click SPC Loose Lay, Perimeter Glue, or Full Spread Adhesive
Installation Layout	Ashlar or a minimum 6" short-joint stagger


PERFORMANCE

Floor Score Certified	Yes
Ortho-Phthalate Free	Yes
Warranty	Commercial 10 Year Limited Residential Lifetime Limited

PACKAGING

Square Feet Per Carton	9" x 60" - 22.5 f ² SPC 21.45 f ² LL
Pieces Per Carton	9" x 60" - 6 pcs SPC 6 pcs LL
Pounds Per Carton	9" x 60" - 35.49 lbs SPC 41.67 lbs LL

COORDINATING TRIM



T-MOLDING



REDUCER



FLUSH STAIR NOSE



ARISTO	ALABASTER	FAWN	AMBER	WHEAT	MINK
9" x 60" SPC	EL905	EL855	EL865	EL875	EL895
9" x 60" LL	EL906	EL856	EL866	EL876	EL896
Flush Stair Nose	EL909	EL862	EL872	EL882	EL902
Reducer	EL908	EL859	EL869	EL879	EL899
T-Molding	EL907	EL858	EL868	EL878	EL898