



PRODUCT

Construction	SPC Rigid Core
Sizes	12" x 24" SPC 18" x 36" SPC
Total Thickness	6.5 mm SPC
Wear Layer	20 mil
Protective Coating	UV, Stain, & Scratch
Attached Pad	1.5 mm High Density IXPE Sound Abatement SPC
Edge Profile	Painted Bevel
Installation Method	Rigid Core Floating Click SPC
Installation Layout	Ashlar or a minimum 6" short-joint stagger



PERFORMANCE

Floor Score Certified	Yes
Ortho-Phthalate Free	Yes
Warranty	Commercial 10 Year Limited Residential Lifetime Limited

PACKAGING

Square Feet Per Carton	12" x 24" - 16.02 f ² SPC 18" x 36" - 27 f ² SPC
Pieces Per Carton	12" x 24" - 8 pcs SPC 18" x 36" - 6 pcs SPC
Pounds Per Carton	12" x 24" - 34.45 lbs SPC 18" x 36" - 55.65 lbs SPC


COORDINATING TRIM



T-MOLDING



REDUCER



FLUSH STAIR NOSE

CALACATTA	BIANCO
12" x 24" SPC	EL440
18" x 36" SPC	EL441
T-Molding	EL443
Reducer	EL444
Flush Stair Nose	EL447