



PRODUCT

Construction	SPC Rigid Core
Sizes	7" x 48"
Total Thickness	6.5 mm SPC
Wear Layer	20 mil
Surface	Emboss in Register
Protective Coating	UV, Stain, & Scratch
Attached Pad	1.5 mm High Density IXPE Sound Abatement SPC
Edge Profile	Micro Bevel
Installation Method	Rigid Core Floating Click SPC
Installation Layout	End joints offset by atleast 6", staggered random

PERFORMANCE

Floor Score Certified	Yes
Ortho-Phthalate Free	Yes
Warranty	Commercial 10 Year Limited Residential Lifetime Limited

PACKAGING

Square Feet Per Carton	7" x 48" - 18.91 f ² SPC
Pieces Per Carton	7" x 48" - 8 pcs SPC
Pounds Per Carton	7" x 48" - 37.3 lbs SPC

COORDINATING TRIM



Q. ROUND



T-MOLDING



REDUCER



END CAP



OVERLAP STAIR NOSE



FLUSH STAIR NOSE

CAMBRIDGE	GREY	WHITE	NATURAL	WHEAT	SADDLE	COFFEE
7" x 48" SPC	EL110	EL100	EL130	EL120	EL140	EL150
Quarter Round	EL111	EL101	EL131	EL121	EL141	EL151
T-Molding	EL112	EL102	EL132	EL122	EL142	EL152
Reducer	EL113	EL103	EL133	EL123	EL143	EL153
End Cap	EL114	EL104	EL134	EL124	EL144	EL154
Overlap Stair Nose	EL115	EL105	EL135	EL125	EL145	EL155
Flush Stair Nose	EL116	EL106	EL136	EL126	EL146	EL156