



## PRODUCT

Construction	SPC Rigid Core   Loose Lay
Sizes	9" x 60"
Total Thickness	5.2mm SPC   5.0mm LL
Wear Layer	20mil
Protective Coating	UV, Stain, & Scratch
Attached Pad	1mm High Density IXPE Sound Abatement SPC
Edge Profile	Micro Bevel
Installation Method	Rigid Core Floating Click SPC   Loose Lay, Perimeter Glue, or Full Spread Adhesive
Installation Layout	Ashlar or a minimum 6" short-joint stagger

## PERFORMANCE

Floor Score Certified	Yes
Ortho-Phthalate Free	Yes
Warranty	Commercial 10 Year Limited Residential Lifetime Limited

## PACKAGING

Square Feet Per Carton	9" x 60" - 22.5 f <sup>2</sup> SPC   21.45 f <sup>2</sup> LL
Pieces Per Carton	9" x 60" - 6 pcs SPC   6 pcs LL
Pounds Per Carton	9" x 60" - 35.49 lbs SPC   41.67 lbs LL

## COORDINATING TRIM



T-MOLDING



REDUCER



FLUSH STAIR NOSE

ENCHANT	FOSSIL	MUSHROOM	SILK	SMOKE	STORMY	SUEDE
9" x 60" SPC	EL725	EL745	EL715	EL755	EL735	EL765
9" x 60" LL	EL726	EL746	EL716	EL756	EL736	EL766
Flush Stair Nose	EL732	EL752	EL722	EL762	EL742	EL772
Reducer	EL729	EL749	EL719	EL759	EL739	EL769
T-Molding	EL728	EL748	EL718	EL758	EL738	EL768