



## PRODUCT

Construction	SPC Rigid Core
Sizes	12" x 24"
Total Thickness	6.5 mm SPC
Wear Layer	20 mil
Surface	Sandy Embossing
Protective Coating	UV, Stain, & Scratch
Attached Pad	1.5 mm High Density IXPE Sound Abatement SPC
Edge Profile	Painted Bevel
Installation Method	Rigid Click
Installation Layout	End joints offset by atleast 6", staggered random

## PERFORMANCE

Floor Score Certified	Yes
Ortho-Phthalate Free	Yes
Warranty	Commercial 10 Year Limited Residential Lifetime Limited

## PACKAGING

Square Feet Per Carton	12" x 24" - 16.02 f <sup>2</sup> SPC
Pieces Per Carton	12" x 24" - 8 pcs SPC
Pounds Per Carton	12" x 24" - 34.45 lbs SPC

## COORDINATING TRIM



Q. ROUND



T-MOLDING



REDUCER



END CAP



OVERLAP STAIR NOSE



FLUSH STAIR NOSE

KALOS STONE	BIANCO	BLU	CENERE	GRIGIO	NERO
12" x 24" SPC	EL340	EL350	EL360	EL370	EL380
Quarter Round	EL341	EL351	EL361	EL371	EL381
T-Molding	EL342	EL352	EL362	EL372	EL382
Reducer	EL343	EL353	EL363	EL373	EL383
End Cap	EL344	EL354	EL364	EL374	EL384
Overlap Stair Nose	EL345	EL355	EL365	EL375	EL385
Flush Stair Nose	EL346	EL356	EL366	EL376	EL386