



## PRODUCT

Construction	SPC Rigid Core
Sizes	12" x 24" SPC   18" x 36" SPC
Total Thickness	6.5 mm
Wear Layer	20 mil
Protective Coating	UV, Stain, & Scratch
Attached Pad	1.5 mm High Density IXPE Sound Abatement SPC
Edge Profile	Painted Bevel
Installation Method	Rigid Click
Installation Layout	Ashlar or a minimum 6" short-joint stagger

## PERFORMANCE

Floor Score Certified	Yes
Ortho-Phthalate Free	Yes
Warranty	Commercial 10 Year Limited Residential Lifetime Limited

## PACKAGING

Square Feet Per Carton	12" x 24" - 20 f <sup>2</sup> SPC   18" x 36" - 27 f <sup>2</sup> SPC
Pieces Per Carton	12" x 24" - 10 pcs SPC   18" x 36" - 6 f <sup>2</sup> SPC
Pounds Per Carton	12" x 24" - 41.23 lbs SPC   18" x 36" 55.6 lbs SPC

## COORDINATING TRIM



MARYLAND	DUNE	TAUPE	GREY	GRAPHITE
12" x 24" SPC	EL490	EL500	EL510	EL520
18" x 36" SPC	EL492	EL502	EL512	EL522
Quarter Round	EL496	EL506	EL516	EL526
T-Molding	EL498	EL508	EL518	EL528
Reducer	EL497	EL507	EL517	EL527
End Cap	EL493	EL503	EL513	EL523
Overlap Stair Nose	EL495	EL505	EL515	EL525
Flush Stair Nose	EL494	EL504	EL514	EL524