



PRODUCT

Construction	SPC Rigid Core
Sizes	7" x 48"
Total Thickness	6.5 mm SPC
Wear Layer	20 mil
Surface	Emboss in Register
Protective Coating	UV, Stain, & Scratch
Attached Pad	1.5 mm High Density IXPE Sound Abatement SPC
Edge Profile	Micro Bevel
Installation Method	Rigid Click
Installation Layout	End joints offset by atleast 6", staggered random

PERFORMANCE

Floor Score Certified	Yes
Ortho-Phthalate Free	Yes
Warranty	Commercial 10 Year Limited Residential Lifetime Limited

PACKAGING

Square Feet Per Carton	7" x 48" - 14.18 f ² SPC
Pieces Per Carton	7" x 48" - 6 pcs SPC
Pounds Per Carton	7" x 48" - 30.8 lbs SPC

COORDINATING TRIM



Q. ROUND



T-MOLDING



REDUCER



END CAP



OVERLAP STAIR NOSE



FLUSH STAIR NOSE

MAUI	OCEAN	MIST	ASH	DRIFT	TEAK	JAVA
7" x 48" SPC	EL300	EL310	EL320	EL280	EL290	EL330
Quarter Round	EL301	EL311	EL321	EL281	EL291	EL331
T-Molding	EL302	EL312	EL322	EL282	EL292	EL332
Reducer	EL303	EL313	EL323	EL283	EL293	EL333
End Cap	EL304	EL314	EL324	EL284	EL294	EL334
Overlap Stair Nose	EL305	EL315	EL325	EL285	EL295	EL335
Flush Stair Nose	EL306	EL316	EL326	EL286	EL296	EL336