



PRODUCT

Construction	SPC Rigid Core
Sizes	12" x 24"
Total Thickness	6.5 mm SPC
Wear Layer	20 mil
Surface	Sandy Embossing
Protective Coating	UV, Stain, & Scratch
Attached Pad	High Density IXPE Sound Abatement SPC
Edge Profile	Painted Bevel
Installation Method	Rigid Core Floating Click SPC
Installation Layout	Ashlar or a minimum 6" short-joint stagger

PERFORMANCE

Floor Score Certified	Yes
Ortho-Phthalate Free	Yes
Warranty	Commercial 10 Year Limited Residential Lifetime Limited

PACKAGING

Square Feet Per Carton	12" x 24" - 16.02 f ² SPC
Pieces Per Carton	12" x 24" - 8 pcs SPC
Pounds Per Carton	12" x 24" - 34.45 lbs SPC

COORDINATING TRIM



Q. ROUND



T-MOLDING



REDUCER



END CAP



OVERLAP STAIR NOSE



FLUSH STAIR NOSE

SANTA FE	SILVER	RIVER	DESERT	ADOBE	CANYON
12" x 24" SPC	EL390	EL400	EL410	EL420	EL430
Quarter Round	EL391	EL401	EL411	EL421	EL431
T-Molding	EL392	EL402	EL412	EL422	EL432
Reducer	EL393	EL403	EL413	EL423	EL433
End Cap	EL394	EL404	EL414	EL424	EL434
Overlap Stair Nose	EL495	EL405	EL415	EL425	EL435
Flush Stair Nose	EL396	EL406	EL416	EL426	EL436