



## PRODUCT

Construction	SPC Rigid Core   Loose Lay
Sizes	9" x 60" SPC   9" x 60" LL
Total Thickness	5.2 mm SPC   5 mm LL
Wear Layer	20 mil
Protective Coating	UV, Stain, & Scratch
Attached Pad	1.5 mm High Density IXPE Sound Abatement SPC
Edge Profile	Micro Bevel
Installation Method	Rigid Core Floating Click SPC   Loose Lay, Perimeter Glue, or Full Spread Adhesive
Installation Layout	Ashlar or a minimum 6" short-joint stagger

## PERFORMANCE

Floor Score Certified	Yes
Ortho-Phthalate Free	Yes
Warranty	Commercial 10 Year Limited Residential Lifetime Limited

## PACKAGING

Square Feet Per Carton	9" x 60" - 21.45 f <sup>2</sup> SPC   22.5 f <sup>2</sup> LL
Pieces Per Carton	9" x 60" - 6 pcs SPC   6 pcs LL
Pounds Per Carton	9" x 60" - 35.49 lbs SPC   41.67 lbs LL

## COORDINATING TRIM



T-MOLDING



REDUCER



FLUSH STAIR NOSE

SOLIDITY	ABALONE	BUFF	CHINCHILLA	EBONY	PASHMINA	TAWNY	TRUFFLE
9" x 60" SPC	EL785	EL805	EL795	EL845	EL825	EL815	EL835
9" x 60" LL	EL786	EL806	EL796	EL846	EL826	EL816	EL836
Flush Stair Nose	EL792	EL812	EL802	EL852	EL832	EL822	EL842
Reducer	EL789	EL809	EL799	EL849	EL829	EL819	EL839
T-Molding	EL788	EL808	EL798	EL848	EL828	EL818	EL838