




















ABOVE: TERRA
COVER: ICE

	Technical Specifications	Standard Requirements	Test Results
	Water Absorption UNI EN ISO 10545-03	E ≤ 0.5%	0.2% - 0.5%
	Breaking Strength UNI EN ISO 10545-04	≥1300 N	1500 N - 1700 N
	Modulus of Rupture UNI EN ISO 10545-04	> 35 N/mm²	40 N/mm² - 50 N/mm²
	Shock Resistance UNI EN ISO 10545-05	Suggested Minimum: E > 0.55	0.87 - 0.89
	Resistance to Deep Abrasion UNI EN ISO 10545-06	Maximum: 175 mm³	N/A
	Thermal Linear Expansion UNI EN ISO 10545-08	As Reported	< 7 x 10 ⁻⁶ /°C
	Thermal Shock Resistance UNI EN ISO 10545-09	Required	Resistant
	Moisture Expansion UNI EN ISO 10545-10	As Reported	< 0.0 mm/m
	Frost Resistance UNI EN ISO 10545-12	As Reported	Resistant
	Chemical Resistance UNI EN ISO 10545-13	Domestic Chemical Products: UB/ GB Acids and Alkalis: As Reported	GHA
	Stain Resistance UNI EN ISO 10545-14	Minimum: Class 3	Class 5
	PEI Rating (Scratch Resistance) ASTM C 1027	As Reported	IV
	Dynamic Coefficient of Friction (DCOF) ANSI A137.1	For Level Interior Spaces Expected to be Walked Upon When wet: ≥ 0.42	≥ 0.42
	Shade Variation	As Reported	V2
	Thickness	As Reported	12" x 24" - 9 mm 24" x 24" - 9 mm
	Number of Screens	As Reported	12" x 24" - 24 24" x 24" - 12


Grout joint required for rectified edge tile
1/2 broken joint not recommended

1/2 BROKEN JOINT NOT RECOMMENDED




NO

MANUFACTURER RECOMMENDS 1/3 OR LESS STAGGERED SPACING




YES

INSTALLATION TIPS



Recommended
3/16" Grout Joint

1/3 — Overlap should not exceed 33%



Use a leveling system during
installation to reduce lippage







STONE

SALT STONE

PORCELAIN





SALT STONE

The Salt Stone collection is a dynamic combination of natural materials. The look of onyx and salt crystals were brought together to create this nature inspired stone-look tile. The result is a collection that is boldly natural and brilliantly organic.

Available in four colors: terra, desert, ice, and ash, two sizes: 24" x 24" and 12" x 24", and three mosaics: 2" x 2", hexagon, and herringbone this collection is classic in its specifications. Its colors range from a rich red clay inspired hue, to a neutral taupe, a brilliantly toned white, and a beige toned gray. Giving option to a wide range of desired color palettes, Salt Stone is an idyllic range of stone-look tile that embodies the beauty of nature.



ALL FORMATS AVAILABE IN NATURAL FINISH

ICE



24" x 24"



12" x 24"



3" x 24" Bullnose



2" x 2" Mosaic
(12" x 12" Sheet)



Hexagon Mosaic
12" x 13" Sheet
Net Coverage: 1.1 sqft



Herringbone Mosaic
13" x 13" Sheet
Net Coverage: 1 sqft

ASH



24" x 24"



12" x 24"



3" x 24" Bullnose



2" x 2" Mosaic
(12" x 12" Sheet)



Hexagon Mosaic
12" x 13" Sheet
Net Coverage: 1.1 sqft



Herringbone Mosaic
13" x 13" Sheet
Net Coverage: 1 sqft

DESERT



24" x 24"



12" x 24"



3" x 24" Bullnose



2" x 2" Mosaic
(12" x 12" Sheet)




Hexagon Mosaic
12" x 13" Sheet
Net Coverage: 1.1 sqft




Herringbone Mosaic
13" x 13" Sheet
Net Coverage: 1 sqft

TERRA



24" x 24"



12" x 24"



3" x 24" Bullnose



2" x 2" Mosaic
(12" x 12" Sheet)



Hexagon Mosaic
12" x 13" Sheet
Net Coverage: 1.1 sqft



Herringbone Mosaic
13" x 13" Sheet
Net Coverage: 1 sqft

ASH