



PRODUCT

Construction	SPC Rigid Core	Loose Lay
Sizes	9" x 60" SPC	18" x 36"
Total Thickness	5.2 mm SPC	5.0mm
Wear Layer	20 mil	20mil
IIC	68 SPC	60
Protective Coating	UV, Stain, & Scratch	UV, Stain, & Scratch
Attached Pad	1.5 mm High Density IXPE Sound Abatement SPC	-
Edge Profile	Micro Bevel	Micro Bevel
Installation Method	Rigid Core Floating Click SPC	Loose Lay, Perimeter Glue, or Full Spread Adhesive
Installation Layout	Standard or a minimum 6" short-joint stagger	Standard or a minimum 6" short-joint stagger

PERFORMANCE

Floor Score Certified	Yes
Ortho-Phthalate Free	Yes
Warranty	Commercial 10 Year Limited Residential Lifetime Limited

PACKAGING

	9" x 60" SPC	9" x 60" LL
Square Feet Per Carton	21.45 f ²	22.5 f ²
Pieces Per Carton	6 pcs	6 pcs
Pounds Per Carton	35.49 lbs	41.67 lbs

COORDINATING TRIM



ENCHANT	FOSSIL	MUSHROOM	SILK	SMOKE	STORMY	SUEDE
9" x 60" SPC	EL725	EL745	EL715	EL755	EL735	EL765
9" x 60" LL	EL726	EL746	EL716	EL756	EL736	EL766
Flush Stair Nose	EL732	EL752	EL722	EL762	EL742	EL772
Reducer	EL729	EL749	EL719	EL759	EL739	EL769
T-Molding	EL728	EL748	EL718	EL758	EL738	EL768
Overlap Stair Nose	EL731	EL751	EL721	EL761	EL741	EL771
End Cap	EL730	EL750	EL720	EL760	EL740	EL770