

SOLIDITY

SPC RIGID CORE



ABOUT

Solidity captures the mighty Oak's strength and beauty revered by prominent artist for centuries. Proudly demonstrating its tonal variation through swirls of graining, forging pops of distinction attracting the creative eye. Exude class with this rich range of patterning in Easy Luxury Rigid Core and Loose Lay worry-free 9" x 60" plank installation options.

COLORS



ABALONE



CHINCHILLA



BUFF



TAWNY



PASHMINA



TRUFFLE




EBONY

PRODUCT INFO


Construction	SPC Rigid Core
Sizes	9" x 60"
Total Thickness	5.2mm
Wear Layer	20mil
Protective Coating	UV, Stain, & Scratch
Attached Pad	High Density IXPE Sound Abatement Pad
IIC	68
Edge Profile	Micro Bevel
Installation Method	Rigid Core Floating Click
Installation Layout	Random or a minimum 6" short-joint stagger

Floor Score Certified	Yes
Ortho-Phthalate Free	Yes
Warranty	Commercial 10 Year Limited, Residential Lifetime Limited
Size & Tile Type	9" x 60" SPC
Square Feet Per Carton	21.45 f ²
Pieces Per Carton	6 pcs
Pounds Per Carton	35.49 lbs


COORDINATING TRIM



T-MOLDING



REDUCER



FLUSH STAIR NOSE

PRODUCT SKUS

SOLIDITY	ABALONE	BUFF	CHINCHILLA	EBONY	PASHMINA	TAWNY	TRUFFLE
9" x 60" SPC	EL785	EL805	EL795	EL845	EL825	EL815	EL835
T-Molding	EL788	EL808	EL798	EL848	EL828	EL818	EL838
Reducer	EL789	EL809	EL799	EL849	EL829	EL819	EL839
Flush Stair Nose	EL792	EL812	EL802	EL852	EL832	EL822	EL842

SOLIDITY

LOOSE LAY



ABOUT

Solidity captures the mighty Oak's strength and beauty revered by prominent artist for centuries. Proudly demonstrating its tonal variation through swirls of graining, forging pops of distinction attracting the creative eye. Exude class with this rich range of patterning in Easy Luxury Rigid Core and Loose Lay worry-free 9" x 60" plank installation options.

COLORS



ABALONE



CHINCHILLA



BUFF



TAWNY



PASHMINA



TRUFFLE



EBONY

PRODUCT INFO


Construction	Loose Lay
Sizes	9" x 60"
Total Thickness	5.0 mm
Wear Layer	20 mil
Protective Coating	UV, Stain, & Scratch
Attached Pad	N/A
IIC	60
Edge Profile	Micro Bevel
Installation Method	Loose Lay, Perimeter Glue, or Full Spread Adhesive
Installation Layout	Random or a minimum 6" short-joint stagger
Floor Score Certified	Yes
Ortho-Phthalate Free	Yes
Warranty	Commercial 10 Year Limited, Residential Lifetime Limited

Size & Tile Type	9" x 60" LL
Square Feet Per Carton	22.5 f ²
Pieces Per Carton	6 pcs
Pounds Per Carton	41.67 lbs

COORDINATING TRIM



T-MOLDING



REDUCER



FLUSH STAIR NOSE

PRODUCT SKUS

SOLIDITY	ABALONE	BUFF	CHINCHILLA	EBONY	PASHMINA	TAWNY	TRUFFLE
9" x 60" LL	EL786	EL806	EL796	EL846	EL826	EL816	EL836
T-Molding	EL788	EL808	EL798	EL848	EL828	EL818	EL838
Reducer	EL789	EL809	EL799	EL849	EL829	EL819	EL839
Flush Stair Nose	EL792	EL812	EL802	EL852	EL832	EL822	EL842