



















ABOVE : PEARL NATURAL  
COVER: IVORY NATURAL

	Technical Specifications	Standard Requirements	Natural	Polished
	Water Absorption UNI EN ISO 10545-03	E ≤ 0.5%	≤ 0.5%	≤ 0.5%
	Breaking Strength UNI EN ISO 10545-04	≥ 1300 N	≥ 1300 N	≥ 1300 N
	Modulus of Rupture UNI EN ISO 10545-04	> 35 N/mm²	> 35 N/mm²	> 35 N/mm²
	Shock Resistance UNI EN ISO 10545-05	Suggested Minimum: E > 0.55	N/A	N/A
	Resistance to Deep Abrasion UNI EN ISO 10545-06	Maximum: 175 mm³	Resistant	Resistant
	Thermal Linear Expansion UNI EN ISO 10545-08	As Reported	5.9 x 10 <sup>-6</sup> /°C	5.9 x 10 <sup>-6</sup> /°C
	Thermal Shock Resistance UNI EN ISO 10545-09	Required	Resistant	Resistant
	Moisture Expansion UNI EN ISO 10545-10	As Reported	N/A	N/A
	Frost Resistance UNI EN ISO 10545-12	As Reported	Resistant	Resistant
	Chemical Resistance UNI EN ISO 10545-13	Domestic Chemical Products: UB/ GB Acids and Alkalis: As Reported	Class B	Class B
	Stain Resistance UNI EN ISO 10545-14	Minimum: Class 3	Class 4	Class 5
<b>PEI</b>	PEI Rating (Scratch Resistance) ASTM C 1027	As Reported	Pearl, Ivory: IV Grey: IV	Pearl, Ivory: IV Grey: III
	Dynamic Coefficient of Friction (DCOF) ANSI A137.1	For Level Interior Spaces Expected to be Walked Upon When wet: ≥ 0.42	≥ 0.42	N/A
	Shade Variation	As Reported	V3	V3
	Thickness	As Reported	12" x 24" - 8.7 mm 30" x 30" - 9.7 mm 24" x 48" - 9 mm	24" x 48" - 10.5 mm
	Number of Screens	As Reported	12" x 24" - 23 30" x 30" - 13 24" x 48" - 11	24" x 48" - 11



Grout joint required for rectified edge tile  
1/2 broken joint not recommended



MANUFACTURER RECOMMENDS 1/3 OR LESS STAGGERED SPACING



#### INSTALLATION TIPS



Use a leveling system during  
installation to reduce lippage



HAPPY FLOORS



≥ 15%



STONE



# AUSTRAL

GLAZED PORCELAIN





WALL: GREY NATURAL  
FLOOR: PEARL NATURAL

# AUSTRAL

Our most resourceful sandstone-look is available in a variety of colors: Pearl, Grey, and Ivory. This classy collection comes with well-defined graphics based on stones found, as its name implies, in the southern hemisphere. These Austral graphics invoke the spirit behind this beautiful design. This lustrous collection creates lasting sophistication for any space.



WALL: PEARL POLISHED  
FLOOR: GREY POLISHED

## PEARL



24" x 48" RECTIFIED  
(Natural/ Polished)



30" x 30" RECTIFIED  
(Natural)



12" x 24" RECTIFIED  
(Natural)



2" x 2" Mosaic  
12" x 12" Sheet  
(Natural)



3" x 3" Hexagon Mosaic  
8" x 10" Sheet  
Net Coverage: 0.59 sqft  
(Natural)



3" x 24" Bullnose  
(Natural/Polished)

## IVORY



24" x 48" RECTIFIED  
(Natural/ Polished)



30" x 30" RECTIFIED  
(Natural)




12" x 24" RECTIFIED  
(Natural)



2" x 2" Mosaic  
12" x 12" Sheet  
(Natural)




3" x 3" Hexagon Mosaic  
8" x 10" Sheet  
Net Coverage: 0.59 sqft  
(Natural)




3" x 24" Bullnose  
(Natural/Polished)


## GREY



24" x 48" RECTIFIED  
(Natural/ Polished)



30" x 30" RECTIFIED  
(Natural)



12" x 24" RECTIFIED  
(Natural)



2" x 2" Mosaic  
12" x 12" Sheet  
(Natural)



3" x 3" Hexagon Mosaic  
8" x 10" Sheet  
Net Coverage: 0.59 sqft  
(Natural)



3" x 24" Bullnose  
(Natural/Polished)



IVORY POLISHED



PEARL NATURAL