





ABOVE: SILVER & SILVER PRESS  
COVER: CALM

|            | Technical Specifications                           | Standard Requirements   | Test Results                            |   |
|------------|--|---|---|---|
|            |  |   | PORCELAIN                               | WALL TILE   |
|            | Water Absorption<br>UNI EN ISO 10545-03            | <0.5%   | < 0.5%                                  | > 10%   |
|            | Breaking Strength<br>UNI EN ISO 10545-04           | Minimum: 1300 N   | > 1300 N                                | > 600 N   |
|            | Modulus of Rupture<br>UNI EN ISO 10545-04          | Minimum: 35 N/mm <sup>2</sup>   | > 15 N/mm <sup>2</sup>                  | > 35 N/mm <sup>2</sup>                                      |
|            | Shock Resistance<br>UNI EN ISO 10545-05            | Suggested Minimum: e > 0.55   | N/A                                     | N/A   |
|            | Resistance to Deep Abrasion<br>UNI EN ISO 10545-06 | Maximum: 175 mm <sup>3</sup>  | N/A                                     | N/A   |
|            | Thermal Linear Expansion<br>UNI EN ISO 10545-08    | Minimum for Floor Applications: Class 3                                     | < 6 x 10 <sup>-6</sup> °C <sup>-1</sup> | < 6 x 10 <sup>-6</sup> °C <sup>-1</sup>                     |
|            | Thermal Shock Resistance<br>UNI EN ISO 10545-09    | Resistant   | Resistant                               | Resistant   |
|            | Moisture Expansion<br>UNI EN ISO 10545-10          | As Reported   | N/A                                     | N/A   |
|            | Frost Resistance<br>UNI EN ISO 10545-12            | As Reported   | Resistant                               | Resistant   |
|            | Chemical Resistance<br>UNI EN ISO 10545-13         | Domestic Chemical Products:<br>UB/GB Acids and Alkalis:<br>As Reported      | A<br>LA                                 | A<br>LA   |
|            | Stain Resistance<br>UNI EN ISO 10545-14            | Minimum: Class 3  | 5                                       | 5   |
| <b>PEI</b> | PEI Rating (Scratch Resistance)<br>ASTM C 1027     | As Reported   | PEI IV                                  | PEI IV  |
|            | Dynamic Coefficient of Friction (DCOF) ANSI A137.1 | For Level Interior Spaces<br>Expected to be Walked Upon<br>When wet: ≥ 0.42 | ≥ 0.52                                  | ≥ 0.52  |
|            | Shade Variation                                    | As Reported   | V1                                      | V1  |
|            | Thickness  | As Reported   | 9 mm                                    | 9 mm  |
|            | Number of Screens                                  | As Reported   | 12" x 24" - 60<br>24" x 24" - 30        | 16" x 48" - 6<br>16" x 48" Decor - 6<br>16" x 48" Press - 1 |



Grout joint required for rectified edge tile 1/2 broken joint not recommended



MANUFACTURER RECOMMENDS 1/3 OR LESS STAGGERED SPACING



INSTALLATION TIPS



Use a leveling system during installation to reduce lippage



HAPPY FLOORS



DIGITAL INKJET TILE



≥ 20%



The data refers to first choice material in the natural version.



FABRIC

# FIBRA

RECTIFIED PORCELAIN &  
WHITE BODY CERAMIC WALL TILE



# FIBRA




As indicated by its name, Fibra is a contemporary take on Fabric-look tile. This collection isn't intimidated to utilize bold décor pieces, in conjunction with soft tones and subtle colors. This clean looking collection can bring a new aesthetic to any space.




CALM  
CALM PRESS

## Pale

Porcelain Tiles






Wall Tiles



## Calm

Porcelain Tiles






Wall Tiles




## Silver

Porcelain Tiles



Wall Tiles



SILVER DECOR



PALE  
PALE DECOR